



CUTARO SR1100

Mowing nimble and gently

- ✓ High area performance with 11m working width and 350HP
- ✓ Very gentle on the ground due to the very low operating weight
- ✓ Mower disc speed is continuously adjustable
- ✓ The tine conditioner can be switched on/off (insect-friendly)
- ✓ Trailed mower guidance with hydropneumatic relief
- ✓ Air-suspended driver's cab
- ✓ Active radiator cleaning
- ✓ Cutting high hydraulically adjustable
- ✓ Swath former hydraulically adjustable
- ✓ Protective cloths hydraulically foldable up
- ✓ Optimized hydraulic and control concept
- ✓ Great fuel savings due to unique drive concept
- ✓ Economical driving on the road and in the field by reducing the number of rotations
- ✓ Suitable for slopes, large and small plots and difficult soil conditions

Key data

- | | |
|-------------------------------------|--|
| ✓ Working width/ incl. overcut | 11.0m |
| ✓ Total weight/ incl. mower units | 8.5t |
| ✓ Diesel engine | 260kW (350HP), Mercedes 7.7 liters |
| ✓ Disc cutter bar | 8 discs at the front, 9 discs on each side |
| ✓ Tine conditioner | Spring-loaded steel tines/ stepless and reversibel |
| ✓ Dimension/ basic vehicle | 5.10 x 2.97 x 3.24 m (LxWxH) |
| ✓ Dimension/ road incl. mower units | 6.35 x 3.40 x 3.40 m (LxWxH) |
| ✓ Front tires | 710/50R 26.5 |
| ✓ Rear tires | 560/45R 22.5 |
| ✓ Driving speed | Road 30km/h or 40km/h |
| ✓ Diesel tank | 380 liters |
| ✓ AdBlue | 40 liters |